

Engineering Division

GENERAL CONDITIONS FOR TRANSPORTATION PERMITS

Authority

Under the appropriate authority of Division 15, Chapter 5, Article 6 of the California Vehicle Code (CVC), the County of Tuolumne, Public Works Department may, at its discretion, issue special permits to operate or move a vehicle or combination of vehicles or special mobile equipment of a size or weight of vehicle or load exceeding the maximums specified in the CVC. Except as specifically provided herein, the requirements of the CVC, including vehicle registration requirements, signing (CVC 27900) and other applicable laws, must be complied with in all particulars.

Pre-paid permits are valid for two (2) years from date of purchase. The Permittee may request a one (1) year extension on all unused permits prior to original expiration date. Only one extension will be granted. All unused expired pre-paid permits will be considered non-refundable and be destroyed.

Permit Conditions

1. Validity of Permit

This permit is valid only for movement on the assigned County highways and over crossings under the jurisdiction of the Public Works Department and on alternate routes and detours signed as such and approved by the Agency. State permits where appropriate must be secured for travel on roads and streets under their respective jurisdictions unless otherwise specified on the permit.

2. Possession of Permit

This permit shall be carried in the vehicle to which it refers at all times while the vehicle is being moved within the highway limits, and shall be open to inspection by any peace officer, traffic officer, authorized agent of the County of Tuolumne, Public Works Department or any other officer or employee charged with the care and protection of such highways (CVC 35783).

3. Void Permit

This permit is null and void and hereby declared nonexistent if:

- a. Any portion, part or section is illegible.
- b. It is not signed by an authorized representative of the County of Tuolumne, Public Works Department.
- c. Any portion, part or section has been altered or if an attempt to alter is apparent.
- d. Presented in the form of a reproduced copy, other than an "authorized facsimile copy". Annual permits are allowed only in the original form. No reproduced copies are allowed.
- e. Used to represent proper authority for carrying a load and/or moving a vehicle which is not specifically described on the face of the permit.
- f. Used to represent proper authority for carrying a load or moving a vehicle by any company, crew, or equipment not specifically named or organizationally related to the company, agency, or firm to which the permit was issued.
- g. Presented without the attachments firmly affixed that are, specifically, named and required upon the face of the permit.
- h. Used to represent proper authority for carrying a load or moving a vehicle before and/or after the times and dates authorized.

Revised: October 2019 Page 1 of 6



Engineering Division

4. Permittee Agreement

Acceptance constitutes an agreement by the permittee to observe and comply with all of the general and specific conditions on the face of the permit and attachments thereto.

5. Verification

The use of this permit is prima facie evidence that the driver has checked the load and/or vehicle and knows it to be within the limits as set forth hereon and has verified the routing accuracy. The vehicle and/or load authorized under this permit are subject to inspection by representatives of the County of Tuolumne, Public Works Department and costs of such inspection shall be borne by the permittee.

6. Overhead Clearance

When height of load exceeds legal limit, it becomes the responsibility of the permittee to check all underpasses, bridges, overhead wires or other structures for impaired vertical clearance and to bypass to arrange clearance at such locations.

7. Liabilities

The permittee is responsible for all liability for injury to, or death of any person, or damage to property which may occur through any act or omission of either the permittee of the County of Tuolumne arising from the issuance of this permit. In the event any claim, suit or action is brought against the County of Tuolumne, its officers, employees or agents thereof, by reason of, or in connection with any such act or omission, permittee shall defend, indemnify, and hold harmless the County, its officers, employees or agents from such claim, suit or action.

8. Repair of Damage

In accepting this permit, the permittee agrees to repair at his own expense and to the satisfaction of the Director of the Public Works Department, County of Tuolumne, any damage to highway appurtenances or structures. Notwithstanding, work or repair may be done by the Public Works Department forces at the option of the Director, the cost to be borne by the permittee. In the event of damage to County highway facilities such as bridges, traffic signals, light standards and other appurtenances, a written report must be filed with the Public Works Department within 72 hours after such damage has been done. Failure to make this report will be considered cause for cancellation of all permit privileges pending a satisfactory arrangement with the Agency for repair or replacement of the damaged facility.

9. Accident Reporting

Accidents occurring while operating under permit and requiring a report to the Department of Motor Vehicles under CVC Section 16000 shall also be reported to County of Tuolumne. A copy of the permit and accident report shall be mailed to County of Tuolumne, Department of Public Works, 2 South Green Street, Sonora CA 95370.

10. Reducible Loads

This permit is issued for the movement of an "Extralegal Load" as defined in CVC 320.5 when loaded at its least dimensions.

This permit is automatically canceled if the permitted dimensions and weight can be reduced to legal limits by repositioning and/or practical removal of a part, portion, or unit therefrom.

11. Moving in Inclement Weather

Movement shall not occur in snow, fog, rain or wind when visibility is restricted to less the 1,000 feet. Movement is prohibited when road surfaces are hazardous due to rain, ice, snow or frost, or when use of tire chains is mandatory. No moving shall be done when the velocity of the wind is such that it causes the vehicle being towed to whip or swerve from side-to-side or fail to follow substantially in the path of the towing vehicle. Any accident caused by excessive wind or weather conditions shall be considered a prima facie violation of this condition.

Revised: October 2019 Page 2 of 6



Engineering Division

12. Land Use

Where practical, the vehicle shall be kept in the far right lane of the highway and shall not encroach on highway shoulders except where necessary to allow trailing traffic to pass.

13. Scales and Inspection Facilities

Every driver of an extralegal vehicle when operating on a County highway shall be subject to CVC 2813 and stop at all operational scales and inspection facilities.

14. Booster Type Axles

A booster axle is an axle, generally, having an air or hydraulic cylinder suspension system that can be actuated independently to assume a portion of the weight that would otherwise be carried by adjacent axles. Booster axles and add-on or "Joe Dog" axles shall not be used in the movement of overweight permit loads.

15. Movement in Convoy

Movement in convoy shall not be permitted unless specified on the face of the permit.

16. Towing Disabled Permit Vehicles

Disabled vehicles or combination of vehicles whose movement is authorized by a transportation permit or any disabled vehicle or combination of vehicles which because of damage has incurred distortion in width or height thereby causing an excess in legal dimensions may only be moved at the direction of a peace officer or single trip permit issued by the County of Tuolumne, Public Works Department.

Disabled legal vehicles or combination of vehicles, when connected to a tow car may exceed legal gross weight. When one end of a truck or truck tractor of legal weight is elevated by a tow car, the drive axles, the tow car and/or the drive axle or axles of the disabled vehicle may exceed legal axles or group weight limitations. If any axle or axle group exceeds legal weight, movement is limited to the routes or area shown on the Attachment B.

17. Tire Capacity

Permitted axle or axle group weights shall not exceed the rated capacity of vehicle tires except as allowed by California Code of Regulations Title 13, commencing Section 1085 of Article 14. Permitted axle or axle group weights shall not exceed the rated capacity marked on the tire sidewall.

18. Load Signs

All loads or vehicles being moved on County highways which exceed 8'6" in width, 80' in length, or more than 10' of over-hang shall display appropriate warning signs.

Signs shall be posted on front and rear and shall read, "LONG LOAD" or "OVERSIZE". The "LONG LOAD" sign shall be used whenever overall length exceeds 100 feet. The "OVERSIZE" sign shall be used for shorter lengths and other oversize features. The more definitive signs reading "WIDE LOAD", "LONG LOAD", "OVERSIZE LOAD", "EXCESSIVE FRONT OVERHANG" or "EXCESSIVE REAR OVERHANG" may be substituted for the "OVERSIZE" sign when appropriate. The "LONG LOAD" sign shall have preference when length exceeds 100 feet and other over-size features exist. The lettering shall be a 10-inch minimum height with a 1-5/8 inch minimum brush stroke, and a minimum 1 inch margin all around. All signs shall be black letters on a yellow background, mounted at least 18 inches above the road surface front and rear. Signs shall be neat, clean, legible, mounted securely and visible from straight ahead or behind and to 45 degrees either side thereof.

19. Movement During Darkness

"Darkness" is defined in Section 280 of the CVC as being "...any time from one-half hour after sunset to one-half hour before sunrise...". Reference to "sunset" and/or "sunrise" on the face of the permit includes this said one-half hour grace period before and after sunrise and sunset. Movement is not allowed when visibility is less than 1,000 feet.

Revised: October 2019 Page 3 of 6



Engineering Division

Special Conditions for Holiday Travel

20. Holiday Movement

Unless authorized on the face of this permit, movement is prohibited on the following holidays (or any of these holidays falling on a weekend and celebrated on a weekday):

New Year's Day Martin Luther King Jr. Day President's (3rd Monday in February) Memorial Day (Last Monday in May) Independence Day Labor Day Veteran's Day Thanksgiving Day Christmas Day

When one of the above listed holidays falls on Monday or Friday, permit movements will not be allowed on the holiday nor the immediately preceding or following weekend, unless authorized on the face of the permit.

Restriction on the time of move may be imposed on certain highways where, due to a holiday, a substantial increase in traffic volume is recorded. Alternate routes should be used where available.

Special Conditions for Load and/or Vehicle Escorted by Pilot Car(s)

21. Pilot Car and Equipment

Tuolumne County Pilot Car requirements are as follows:

Loads under 10' do not require pilot cars

Loads 10' to 12' wide require 1 pilot car (front)

Loads 12'1" to 14' wide require 2 pilot cars (1 front, 1 rear)

Loads 14'1" or more in width require 2 pilot cars and escort by California Highway Patrol. (1 front, 1 rear)

Note: The requirement for pilot cars may be varied or waived only upon the discretion of the Public Works Department.

It shall be the responsibility of the permittee to ensure that pilot car vehicles and operators are equipped and briefed as to their duties prior to movement. Pilot cars shall be single vehicles with a minimum of 60 inches in width and may operate with a nondestructive vertical clearance measuring device with height in excess of 14 feet.

Pilot cars shall be equipped with:

- a. One each STOP/SLOW sign paddle.
- b. One each orange vest, shirt or jacket.
- c. One each red hand flag (18" x 18" minimum).
- d. Two-way radio communication between the pilot car(s) and the transporting vehicle.
- e. Top-mounting flashing amber warning light(s). The light(s) shall be visible to the front when leading and to the rear when following and shall be operated at all times when escorting a permit move. Lights shall be removed or covered with opaque material when not escorting movement described movement described on Permit (25270).

Revised: October 2019 Page 4 of 6



Engineering Division

CVC).

f. Neat, clean and legible sign(s) visible from straight ahead or behind and to 45 degrees either side thereof. The bottom of the sign(s) shall be a minimum of 48 inches above the ground. The sign shall read "OVERSIZE" when viewed from the front or rear. The more definitive signs reading "OVERSIZE LOAD," "WIDE LOAD," or "LONG LOAD" may be substituted for the "OVERSIZE" sign when appropriate. The sign shall have a bright yellow background with black lettering and have a minimum projected area of 440 square inches. The lettering shall have a one inch minimum brush stroke with a six (6) inch minimum projected letter height.

22. Pilot Car Location and Responsibility

When required on permit, a pilot car shall:

- a. Precede the load on two or three lane conventional roads and follow on four or more lane conventional highways and divided highways. When two pilot cars are required, one shall precede and one shall follow.
- b. Remain right of the centerline of the roadway at all times except when prevented by the physical limitations of the highway. The use of a pilot car does not grant to the permittee the right to pre-empt the opposing traffic lane. When it becomes necessary because of physical limitations of the highway to use a portion of the opposing traffic lane, the permit move shall not occupy that lane until it has been advised by the pilot car that the lane is clear of all oncoming traffic. Opposing traffic is not to be stopped, except in extreme emergencies. It shall be the responsibility of the permit move to stop safely and wait until the opposing lane is free of traffic before proceeding.
- c. Maintain proper interval between load and the pilot car to allow passing by other traffic.
- d. Accompany the permitted load over all operational California Highway Patrol facilities.

A pilot car shall not:

- a. Pre-empt opposing traffic.
- b. Tow another vehicle while being used as a pilot car.
- c. Display the STOP/SLOW sign paddle out of the window of a moving vehicle.
- d. Stop opposing traffic except in extreme emergencies.
- e. Convoy more than one load at the same time.

When necessary to post a flagger in order to warn and direct traffic, the flagging shall be done in accordance with Title 8, Sections 1598 and 1599 of the California Division of Occupational Safety and Health Construction Safety Order and Caltrans "Manual of Traffic Controls". Flaggers shall not be less than 18 years of age.

Revised: October 2019 Page 5 of 6



Engineering Division

Special Conditions for Manufactured Housing

23. Manufactured Housing Axle Weight

Axle weights for "Manufactured Housing" (CVC 387) shall not exceed 6,000 lbs. per axle.

24. Manufactured Housing - Tow Vehicle

Tractor units towing manufactured housing as defined in CVC 387 that exceed legal width and up to 12 feet in width shall be equipped with dual rear wheel and shall have an unladen weight as defined in CVC 660 of not less than 6,500 lbs.

Tractor units towing manufactured housing exceeding 12 feet in width shall be equipped as required above with an unladen weight as defined in CVC 660 of not less than 9,500 lbs.

25. Open Side Covering

Open sided units shall be covered by plywood, hard board or other rigid material. In lieu of rigid material, suitable plastics, or other flexible material may be used. Billowing or flapping of plastic or flexible side covering in excess of 6 inches in any one place will not be permitted.

Units open on both sides, such as used for temporary schools, warehouses, offices, etc., may be moved empty with no side covering.

P:\PERMITS\Transportation\Attachments\General Conditions for Transportation permits.docx

Revised: October 2019 Page 6 of 6